

Folding tents Colecti'v series

Easy and fast setting-up. Colecti'v range is designed for intensive use. Eight sides aluminium profile 50mm. Aluminium connecting parts. Stainless steel bolts. 3 qualities of fabric available : PVC 380gr/sqm, PVC 520gr/sqm or nylon polyester Technitex 300gr/sqm.

LEGEND

- 1 Self-locking corner trigger
- 2 Stainless steel bolts
- 3 Injected fiberglass
- 4 Anodized aluminum scissors
- 5 Anodized aluminum profile
- 6 Anodized aluminum middle connector
- 7 Foot plate
- 8 Walls set up with Velcro 50mm and connection between them

AVAILABLE SIZES

- COL330** 3mx3m 9 sqm
COL345 3mx4,5m 13,5 sqm
COL360 3mx6m 18 sqm
COL440 4mx4m 16 sqm

SECURITY REGISTER



Deliver by the prefecture

Applicable regulations
 art R 123-51 C.C.H.
 art 175-30
 stop of 23.01.85

Blank wall



Completely opaque

Door wall



Central door double ZIP
 fastener passage of 90cm

Semi-panoramic wall*



and enclosed curtain

The Colecti'V walls

The Colecti'v walls are supplied as a full set for quality Technitex, and by numeral count for quality PVC 380 and 520gr/sqm.

* Only available in PVC 380/sqm and 520/sqm quality.

	Weight	Measurements when folded	Height of peak	Number of legs	Number of peaks	Surface	Height under flap
COL330	30kg	1,52x0,25x0,25	3,15m	4	1	9s qm	1,90 à 2,05m
COL345	36kg	1,52x0,31x0,31	3,15m	4	2	13,5 sqm	1,90 à 2,05m
COL360	49kg	1,52x0,31x0,47	3,15m	6	3	18 sqm	1,90 à 2,05m
COL440	42kg	1,52x0,40x0,40	3,15m	4	1	16 sqm	1,90 à 2,05m



PACK CONTENTS

Frame, top and technical protective cover.



ADVANTAGES Colecti'V

Regular use

2 years warranty
European safety standard
Aluminum frame

Approvable CTS

according to the NV 1965 standard

Wind resistance : +70km/h

(with proper tethering).

Available in 3 fabric qualities :

- > **Technitex® 300gr/sqm**, polyester nylon with PVC one side.
- > **520gr/sqm PVC** fabric M2 fire-resistant.
- > **380gr/sqm PVC** fabric M2 fire-resistant.

AVAILABLE COLORS

> Tarpaulin **Technitex® 300gr/sqm** ★★★★★

PANTONE 7455C

RAL 9016

PANTONE Black C

PANTONE 200C

PANTONE 561C

> Tarpaulin **PVC 520gr/sqm** ★★★★★

RAL 9016



> Tarpaulin **PVC 380gr/sqm** ★★★★★



RAL 2007

RAL 9016

RAL 1023

RAL Coca Cola

RAL 7042

RAL 6005

RAL 9011

RAL 5005

RAL 1015

- 1 Tarpaulin reinforced on each corner.
- 2 Backing and strap on the cross brace.
- 3 Velcro 50mm.
- 4 Reinforcement on the upper section.