

Folding tents **ECO** series

These tents are recommended for occasional and average intensity use. Easy corner locking system pull pin joints. Frame in metal alloy anti-rust epoxy painting. Injected nylon connector piece. Steel bolts.

LEGEND

- 1 Injected nylon connector
- 2 Metal bolts
- 3 Superior part of foot
- 4 Scissors in metal alloy anti-rust epoxy painting
- 5 Profile in metal alloy anti-rust epoxy painting
- 6 Height adjustment
- 7 Walls set up with Velcro 50mm and connectors between them

AVAILABLE SIZES

- ECO330** 3mx3m 9 sqm
ECO345 3mx4,5m 13,5 sqm
ECO360 3mx6m 18 sqm

Blank wall



Completely opaque

Door wall



Central Door double ZIP fastener

The ECO walls are supplied as a complete set



- > **ECO330 Walls pack** :
Three 3m blank walls and one 3m door wall.
- > **ECO345 Walls pack** :
Two 4,5m blank walls, One 3m blank wall and one 3m door wall.
- > **ECO360 Walls pack** :
Five 3m blank walls and one 3m door wall.

	Weight	Measurements when folded	Height of peak	Number of legs	Number of peaks	Surface	Height under flap
ECO330	25kg	1,58x0,24x0,24	3,15m	4	1	9 sqm	2,00 à 2,30m
ECO345	32kg	1,58x0,24x0,32	3,15m	4	2	13,5 sqm	2,00 à 2,30m
ECO360	43kg	1,58x0,26x0,42	3,15m	6	3	18 sqm	2,00 à 2,30m



PACK CONTENTS

Frame + top / Carrying bag / Wall bag (optional walls)



FINISH

Perfect aesthetic finish with the wall ties in velcros 50mm.



ADVANTAGES ECO

Value for money

In conformance with directive 98/6/CE

Low flammability fabric

Wind resistance: + 50km/h (with proper tethering)

Soft and resistant fabric **Technitex® 300gr/sqm**, polyester nylon with PVC one side. Hardly flammable, anti UV and 100% waterproof.

AVAILABLE COLORS

RAL 9016


PANTONE Black C

PANTONE 200C

PANTONE 7455C

PANTONE 561C

1



2



3



4



- 1 Tarpaulin reinforced on each corner.
- 2 Backing and strap on the cross brace.
- 3 Velcro 50mm.
- 4 Reinforcement on the upper section.