

Folding tent **XP** range

The XP series is for professionals who have a daily requirement to shelter areas very quickly. The tents are recommended for intensive use and comply with all the relevant safety standards. Injected corner levers facilitate the setting-up and ensure an optimum roof tension. The XP aluminum grooved profiles provide extreme resistance to twisting resulting from assembly (bad weather, wind...).

LEGEND

- 1 Self-locking injected fiber glass corner lever
- 2 Stainless steel bolts
- 3 Injected fiber glass connector
- 4 Foot plate
- 5 Aluminum bracket to protect the fabric
- 6 Aluminum profile diam. 40mm reinforced by grooves
- 7 Aluminum scissors
- 8 Walls setting-up by sliding keder.

AVAILABLE SIZES

- XP220** 2mx2m 4 sqm
XP330 3mx3m 9 sqm
XP345 3mx4,5m 13,5 sqm
XP360 3mx6m 18 sqm

SECURITY REGISTER



Delivered by the prefecture

Applicable regulations
 art R 122-51 C.C.H.
 art 075-36
 step of 23.01.80

Blank wall



Completely opaque

Door wall



Central door double ZIP fastener passage of 90cm

Semi-panoramic wall



With interior encased curtain

Half wall



Possibility to encase the upper side as an option.*

* Supplied with its own tension bar

	Weight	Measurements when folded	Height of peak	Number of legs	Number of peaks	Surface	Height under flap
XP220	27kg	1,52x0,25x0,25	3,15m	4	1	4 sqm	1,90 à 2,05m
XP330	35kg	1,52x0,31x0,31	3,15m	4	1	9 sqm	1,90 à 2,05m
XP345	42kg	1,52x0,31x0,41	3,15m	4	2	13,5 sqm	1,90 à 2,05m
XP360	56kg	1,52x0,31x0,50	3,15m	6	3	18 sqm	1,90 à 2,05m

AVAILABLE IN PAGODA SHAPE (cf page 24)

ALL SIZE
AVAILABLE ON
DEMAND



PACK CONTENTS

Frame, top and technical protective cover.



ADVANTAGES XP

Intensive use

5 year warranty
European safety standard **EN13782**
Approvable **CTS according NV 1965**
(snow and wind)
M2 fire-resistant fabric **PVC 380gr/sqm**
Sliding walls with ties
Structure 100% anodized aluminum
Wind resistance: +95km/h
(with proper tethering)

Flexible and resistant PVC fabric with a unique design, treated for ultra violet protection and a lacquered finish which ensures its longevity.
Resistance -30° + 70°C.

AVAILABLE COLORS

			RAL 2007
RAL 9016	RAL 1023	RAL Coca Cola	RAL 7042
RAL 6005	RAL 9011	RAL 5005	RAL 1015

- All XP walls may have an additional tension in bottom part with a ground bar. For a perfectly tension fabric.
- Backing and strap on the cross brace.
- 50mm Velcro.
- Reinforcement and attachment with scissors.
- Finish at the lowest point by Velcro. Fully hermetic tent.
- Steel reinforcement in extremity of keder avoids tearing of fabric when intensive uses.
- Reinforced fabric on each corner.
- Reinforcement on the upper section.

1




2




3



4



5



6



7



8

